



.....Quieting The World

LEED Credits



....Aerogel Energy Conservation

Acoustiblok	Acoustiwool WF-0.125	Acoustiwool TF-0.11	Thermablok	Category Description
LEED for New Construction and Major Renovations v 2.2				
	√	√	√	Minimum Energy Performance
	√	√	√	Optimize Energy Performance
√		√	√	Recycled Content
LEED for Schools 2007				
	√	√	√	Minimum Energy Performance
	√	√	√	Optimize Energy Performance
√		√	√	Recycled Content
√	√	√		Minimum Acoustical Performance
√	√	√		Enhanced Acoustical Performance
√	√	√	√	Mold Prevention
LEED for Core and Shell v 2.0				
	√	√	√	Minimum Energy Performance
	√	√	√	Optimize Energy Performance
√		√	√	Recycled Content

Acoustiblok® - Quieting The World
Sound Isolation Material

- 100% Recyclable
- 40% Pre Consumer Recycled Content
- Highest Mold Resistance Rating
- Meets or Exceeds Acoustic Performance Ratings



**MADE IN
USA**

Thermablok™ - Aerogel Energy Conservation
Thermal Acoustic Isolation Strips

- 100% Recyclable
- 30% Pre Consumer Recycled Content
- Can increase Wall R Value over 40%
- Hydrophobic & Breathable



Acoustiblok, Inc.
6900 Interbay Blvd.
Tampa, FL 33616

Phone: 813.980.1400
Fax: 813.849.6347

sales@acoustiblok.com
www.acoustiblok.com
www.thermablok.com

Acoustiwool™ - TF0.11
Tile Floor Acoustic Underlayment

- 95% Pre Consumer Recycled Content
- Antimicrobial Treatment Inhibits Mold Growth
- R value = 0.46
- Acoustically Tested by Independent Lab



Acoustiwool™ - WF0.125
Wood Floor Acoustic Underlayment

- 100% Sheep's Wool
- Rapidly Renewable Source
- R value = 0.65
- Acoustically Tested by Independent Lab

